794 I P

COLORIS®

In spite of its flexible binding agent, 794 I P is a quick drying, highly pigmented solvent-based stamping ink which provides very good coverage, is colour fast and weather-proof.

Properties:
The imprints remain resilient and do not break off even when the printed substrate deforms highly. This stamping ink can be thinned with thinner 415 and the drying time adjusted with delay agent 794.

Application:
We recommend 794 I P for marking painted and unpainted meal foils, plastic and rubber belts. This stamping dye is particularly durable even on stretchy materials particularly conveyor belts and rubber tubes. A suitability test should be accomplished previously, because too many different qualities are available on the market to allow a reliable recommendation.

Drying time:
<2 min (metal



Viscosity:
medium viscosity, ~70-130 sec
(Ford 4mm cup)

Stamp material:
Rubber or metal

Stamp pad material:
We recommend felt plate pads for 794 I P. In the case of automatic stamping machines, systems with an ink reservoir are preferred.

Thinner/cleaner:
Thinner 415

Available standard sizes:
50ml/g · 250ml/g · 1000ml/g

01	02	03	04	05	07	21

Opaque

Tampereen Leimasintehdas
www.tampereenleimasintehdas.fi
myynti@tampereenleimasintehdas.fi
puh. 045 1145 541